



IECEX Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification System for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.: **IECEX CML 20.0038X** Page 1 of 3 [Certificate history:](#)

Status: **Current** Issue No: 0

Date of Issue: 2020-05-28

Applicant: **CMP Products Ltd**
36 Nelson Way, Nelson Park East, Cramlington, NE23 1WH
United Kingdom

Equipment: **717 Range of Stopping Plugs**

Optional accessory:

Type of Protection: **Increased Safety "eb", Dust Ignition "ta"**

Marking: Ex eb IIC Gb
Ex ta IIIC Da

Ts= -60°C to +95°C

IP66, IP67, IP68*, IP69, IP69K
**With sealing washer (30m for 16 hours). Without sealing washer (1.1m for 5 days)*

Approved for issue on behalf of the IECEx
Certification Body:

R C Marshall

Position:

Certification Officer

Signature:
(for printed version)

Date:

2020-05-28

1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting www.iecex.com or use of this QR Code.



Certificate issued by:

Eurofins E&E CML Limited
Unit 1, Newport Business Park
New Port Road
Ellesmere Port, CH65 4LZ
United Kingdom





IECEX Certificate of Conformity

Certificate No.: **IECEX CML 20.0038X**

Page 2 of 3

Date of issue: 2020-05-28

Issue No: 0

Manufacturer: **CMP Products Ltd**
36 Nelson Way, Nelson Park East, Cramlington, NE23 1WH
United Kingdom

Additional
manufacturing
locations:

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended

STANDARDS :

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

IEC 60079-0:2017 Explosive atmospheres - Part 0: Equipment - General requirements
Edition:7.0

IEC 60079-31:2013 Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t"
Edition:2

IEC 60079-7:2017 Explosive atmospheres - Part 7: Equipment protection by increased safety "e"
Edition:5.1

This Certificate **does not** indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Report:

[GB/CML/ExTR20.0044/00](#)

Quality Assessment Report:

[GB/CML/QAR19.0001/00](#)



IECEX Certificate of Conformity

Certificate No.: **IECEX CML 20.0038X**

Page 3 of 3

Date of issue: 2020-05-28

Issue No: 0

EQUIPMENT:

Equipment and systems covered by this Certificate are as follows:

The Type 717/717e/717E Range of Stopping Plugs are manufactured from a non-metallic material and comprise a cylindrical body with an external male thread along their length with the exception of a portion at one end. Each has a socket head recess, an external hexagon, and also a screwdriver slot for fitting and removal.

Refer to Annex for full description and conditions of manufacture.

SPECIFIC CONDITIONS OF USE: YES as shown below:

Refer to Annex for specific conditions of use.

Annex:

[IECEX CML 20.0038X Iss. 0 Certificate Annex_1.pdf](#)

Annexe to: IECEx CML 20.0038X Issue 0
Applicant: CMP Products Ltd
Apparatus: 717 Range of Stopping Plugs



Description

The Type 717/717e/717E Range of Stopping Plugs are manufactured from a non-metallic material and comprise a cylindrical body with an external male thread along their length with the exception of a portion at one end. Each has a socket head recess, an external hexagon, and also a screwdriver slot for fitting and removal.

The Stopping Plugs have a service temperature range of -60°C to +95°C, and are available in the sizes referenced in the below table:

Thread Size
M20
M25
M32
1/2" NPT
3/4" NPT
1" NPT

Conditions of Manufacture

None.

Specific Conditions of Use

The following conditions relate to the installation and/or safe use of the equipment:

- i. The installer shall refer to the manufacturer's instructions for the action necessary regarding the electrostatic risk associated with the non-metallic stopping plugs.

Unit 1, Newport Business Park
New Port Road
Ellesmere Port
CH65 4LZ

T +44 (0) 151 559 1160
E info@cmllex.com

www.cmllex.com

Company Reg No. 8554022 VAT No. GB163023642

